# DECLAN SERIES FLOOD LIGHT

#### **KEY FEATURES**

### **BODY**

Powder painted noncorrosive high-pressure die-case aluminium

#### **OPTIC**

Symmetric glare-free optic

Narrow beam (NB) 45°


Wide beam (WB) 90°

### **LED**

High power LED OSRAM OSLON SQUARE



## DIMENSIONS



MODEL	A(mm)	B(mm)	C(mm)	
OL-DECLAN-M1	700	120	200	
OL-DECLAN-M2	300	230	280	

IP65	230v	OPT TEMP -20 to +50°C	50 HZ	CRI 80	EEC A+	3yrs warranty		T T	CE	RoHS
------	------	-----------------------------	----------	-----------	--------	------------------	--	-----	----	------

## TECHNICAL SPECIFICATION

MODEL NUMBER	W		lm/W	K
OL-DECLAN-M1-NB-01	108	12,800lm	119	
OL-DECLAN-M1-WB-01	108	13,100lm	121	4,000K
OL-DECLAN-M2-NB-01	209	25,500lm	122	5,700K
OL-DECLAN-M2-WB-01	209	26,100lm	125	

## **DATASHEET**



# DECLAN SERIES FLOOD LIGHT

## PHOTOMETRIC DRAWINGS

