

KANE SERIES HIGHBAY LIGHTS

KEY FEATURES

BODY

Powder coated non corrosive high pressure die-cast aluminium.

OPTIC

KC - clear hardened glass (standard)

PC - clear polycarbonate

PCO - opal polycarbonate


LED

Mid power LED

CRI 80 (CRI 90 on request)



DIMENSIONS



MODEL	A(mm)	B(mm)	C(mm)	R(mm)	S(mm)
OL-KANE-M1(C4)	300	300	125	160	200
OL-KANE-M2(C8)	465	465	135	230	290

IP65

220-240V

50-60HZ

CRI >80

EEC A+

max Ta
45 °C

LIFETIME
80,000
HRS

3yrs
Warranty

CE

RoHS


TECHNICAL SPECIFICATION

MODEL NUMBER	W	lm	lm/W	K
OL-KANE-M1(C4)-01	87	12,200lm	140	3,000K 4,000K 5,700K
OL-KANE-M2(C8)-01	173	25,500lm	147	

Fabiia, G08, The Light Box, 111 Power Road, Chiswick, London W4 5PY, United Kingdom.
contact@norse.lighting | www.norse.lighting

KANE SERIES Highbay Lights

PHOTOMETRIC DRAWINGS




OPTIONS



M1/KC
Clear hardened glass (standard)(KC)



M1/PC
Clear polycarbonate (PC)



M1/PCO
Opal polycarbonate (PCO)

ACCESSORIES




/PIR
PIR Sensor



/DALI
DALI

ADDITIONAL PHOTOS



Fabiia, G08, The Light Box, 111 Power Road, Chiswick, London W4 5PY, United Kingdom.
contact@norse.lighting | www.norse.lighting

Please note: Specification values may change due to rapid development of lighting technology. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification.